HARRISON TOWNSHIP CONSTRUCTION OFFICE

114 BRIDGETON PIKE MULLICA HILL, NJ 08062 PHONE: (856)478-6522 FAX: (856)478-6287

RESIDENTIAL DECK CHECKLIST

INFORMA	TION REQUIRED FOR REVIEW:
	PLOT PLAN SHOWING LOCATION OF DECK (TWO COPIES)
	TWO COMPLETE SETS OF PLANS DRAWN AS CLOSE TO SCALE AS POSSIBLE
PLANS WI	LL INCLUDE:
	ELEVATIONS (SIDE VIEW) & AERIAL VIEW (LOOKING DOWN FROM ABOVE)
	HEIGHT OF DECK SURFACE ABOVE GRADE
	DEPTH OF CONCRETE PIERS, 30" MIN. (INCLUDE LAYOUT & SPACING)
	DIAMETER OF CONCRETE PIERS, BASED ON 50 PSF AND SOIL CAPACITY
	SIZE AND LOCATION OF SUPPORT POSTS
	<u>DIAGONAL BRACING REQUIRED</u> , POST TO BEAM, ON ALL DECKS MORE THAN 30 INCHES ABOVE GRADE TO THE DECK SURFACE.
	SIZE AND LOCATION OF SUPPORT BEAMS
	METHOD OF ATTACHEMENT TO EXISTING STRUCTURE, LAG/BOLT SIZE (MIN. ½" DIA.)
	& LENGTH (MIN. 4 ½"), NOTE "OC" SPACING ON LEDGER
	INCLUDE A STATEMENT ON PLAN AS TO WHAT TYPE OF RIM BOARD AND/OR JOIST IS PRESENT ON EXISTING DWELLING WHERE DECK LEDGER WILL BE ATTACHED. LEDGER BOARD MUST BE FASTENED TO SILL PLATE OF HOUSE (NOT ONLY INTO RIM JOIST). PLANS WILL BE REJECTED IF THIS INFORMATION IS NOT INCLUDED!
	SIZE OF JOIST &SPACING (CANTILEVER LENGTH IF ANY)
	TYPE & DIMENSIONS OF DECKING MATERIAL
	. GUARD RAIL DESIGN W/RAIL AND SPINDLE LAYOUT (SPACING BETWEEN SPINDLES OF LESS THAN 4" REQUIRED). MINIMUM HT. 36" GUARD IS REQUIRED IF SURFACE OF DECK IS 30" OR MORE ABOVE GRADE.
	STAIR DETAIL WITH RISER, GUARD AND GRIPRAIL INCLUDED. GRIPRAIL, NOMINAL 2"X 2" REQUIRED ON ONE SIDE OF EACH SET OF STEPS OF FOUR RISERS OR MORE. RISER FACES MUST BE ENCLOSED. CODE REQUIRES A 3/4 TO 11/4 INCH NOSEING ON EACH STAIR TREAD.

NEW JESREY STATE LAW – SUPPLY COST OF CONSTRUCTION OF DECK BASED ON LABOR AND MATERIAL IN ALL CASES

PERMITS REQUIRED – ZONING & BUILDING. ELECTRIC PERMIT – IF WIRING FOR LIGHTING (LOW VOLTAGE OR 120 VOLTS)